

Sensor-switched LED outdoor light

# L 830 SC

Anthracite  
EAN 4007841 055493  
Article number 055493



<b>LED</b>	<b>3000 K</b>								
30 years (Ø 4,5h / day)	3000K warm-white	intelligent high frequency sensor 160°	1 - 5 m	IP44	2 - 2000 lux	5 sec - 60 min	Light source not exchangeable	Control gear not exchangeable	soft light start

## Function description

Digital. Interconnected. Intelligent. The Cube series captivates with a classy look and embellishes any building. With concealed 160° iHF sensor (5 m reach) that only responds to human movement. Night-light function, soft light start and 4-hour manual override (3000 K). Wireless interconnection via Bluetooth, any chosen settings via STEINEL app. Three design options. Available in anthracite, silver and black.

## Technical specifications

Dimensions (L x W x H)	132 x 110 x 110 mm	Reach, radial	r = 5 m (35 m <sup>2</sup> )
With lamp	Yes, STEINEL LED system	Reach, tangential	r = 5 m (35 m <sup>2</sup> )
Manufacturer's Warranty	3 years	Photo-cell controller	Yes
Settings via	Bluetooth, App, Smartphone	Luminous flux total product	493 lm
With remote control	No	Measured luminous flux (360°)	493 lm
Version	Anthracite	Total product efficiency	54 lm/W
PU1, EAN	4007841055493	Colour temperature	3000 K
Application, place	Outdoors	Lamp	LED cannot be replaced
Application, room	outdoors, garden, front door, courtyard & driveway, all round the building, terrace / balcony	LED life expectancy (max. °C)	50000 h
Colour	Anthracite	Service life LED L70B50 (25°)	> 60000 h
includes sheet of self-adhesive numbers	No	Base	without
Installation site	wall	LED cooling system	Passive Thermo Control
Impact resistance	IK03	Soft light start	Yes
IP-rating	IP44	Continuous light	selectable, 4h
Protection class	II	Functions	Motions sensor, Selecting programmed lighting scenarios, Lighting scenario, Night economy mode

Sensor-switched LED outdoor light

# L 830 SC

Anthracite

EAN 4007841 055493

Article number 055493



## Technical specifications

Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	9,1 W
Power consumption	0,44 W
Mounting height max.	2,50 m
Slave modeselectable	Yes
Angle of aperture	160 °
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	Yes
Reach, detail	Detection zone adjustable on 2 axes

Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Main light adjustable	10 - 100 %
Twilight setting TEACH	Yes
Interconnection	Yes
Basic light level function in per cent	10 – 50 %
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
Interconnection via	Bluetooth Mesh Connect
Colour Rendering Index CRI	= 82
Optimum mounting height	2 m

Sensor-switched LED outdoor light

# L 830 SC


Anthracite

EAN 4007841 055493


Article number 055493



## Detection Zone




## Dimension Drawing



Mögliche Montagehöhe: 1,80 m – 2,50 m


Orange: radial und tangential

## Light Distribution Curve



Output	9,1 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Measured luminous flux (360°)	493 lm
Colour temperature	3000 K
Colour Rendering Index	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

## Master/slave interconnection circuit diagram



Sensor-switched LED outdoor light

# L 830 SC

Anthracite

EAN 4007841 055493

Article number 055493



## Master/master interconnection circuit diagram

