

Sensor-switched LED floodlight

# Spot Way SC

with motion detector & Bluetooth  
EAN 4007841 058661  
Article number 058661



LED

20.000 h

3000 K

3000K warm-white



38°



infrared sensor 90°



max. 10 m



twilight switch



IP44



Light source  
replaceable by end  
user



Control gear not  
exchangeable



2 - 1000 lux

## Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

## Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
With lamp	Yes, LED lamp
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Version	with motion detector & Bluetooth
PU1, EAN	4007841058661
Application, place	Outdoors
Application, room	outdoors, garden
Colour	Anthracite
Includes corner wall mount	No
Installation site	Stand mounted
Installation	Stand mounted
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C

Mechanical scalability	No
Reach, radial	r = 2 m (3 m <sup>2</sup> )
Reach, tangential	r = 10 m (79 m <sup>2</sup> )
Photo-cell controller	Yes
Luminous flux total product	512 lm
Measured luminous flux (360°)	512 lm
Total product efficiency	64,8 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Lamp	LED can be replaced
Service life LED L70B50 (25°)	> 20000 h
Soft light start	No
Continuous light	selectable, 4h
Functions	Manual ON / ON-OFF, Timer, Master/slave override
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.

<https://www.steinel.de>

Subject to technical modifications

09.2023 Page 1 from 2

Sensor-switched LED floodlight

# Spot Way SC

with motion detector & Bluetooth  
EAN 4007841 058661  
Article number 058661




## Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave mode/selectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No

Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °

## Detection Zone



Possible mounting height: -  
Orange: radial  
Black: tangential

## Dimension Drawing

